

2mm Cable Fixings Components

2mm Basic Cable Fixings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
C200-2	2.0M (6' 6-3/4") LONG CABLE WITH CEILING FIXINGS - Includes Cable and Ceiling Fixing w/ Standard Base Support	Cable Length: 2M (6' 6-3/4") Top Fixing: 16mm (5/8") Dia.	40kg (88lb) *subject to fixing	Satin Chrome	n/a
KC200-C2P	TOP CABLE FIXING AND PANEL CLAMP - 2.0M (6' 6-3/4") of Cable with Top Fixing and Panel Clamp to take up to 10mm (3/8") thick panel	Cable Length: 2M (6' 6-3/4") Top Fixing: 16mm (5/8") Dia. Bottom Fixing: 19mm (3/4") Dia.	40kg (88lb) *subject to fixing	Satin Chrome	3/32" Standard
C201-4	4.0M (13' 1-1/2") LONG CABLE w/CEILING TO FLOOR FITTINGS AND STANDARD SUPPORTS - Includes Top and Bottom Fixings with Spring Tensioner	Cable Length: 4M (13' 1-1/2") Top & Bottom Fixing: 16mm (5/8") Dia.	120kg (264lb) *subject to fixing	Satin Chrome	1.5mm Metric
C202-4	4.0M (13' 1-1/2") LONG CABLE w/CEILING TO FLOOR FITTINGS AND 25mm (1") Dia. BASE SUPPORTS - Includes Top and Bottom Fixings with Spring Tensioner	Cable Length: 4M (13' 1-1/2") Top Fixing: 16mm (5/8") Dia. Base Plate: 25mm (1") Dia.	120kg (264lb) *subject to fixing	Satin Chrome	1.5mm Metric
C203-4	4.0M (13' 1-1/2") LONG CABLE w/CEILING TO FLOOR FITTINGS AND 38mm (1-1/2") Dia. BASE SUPPORTS - Includes Top and Bottom Fixings with Spring Tensioner	Cable Length: 4M (13' 1-1/2") Top Fixing: 16mm (5/8") Dia. Base Plate: 38MM (1-1/2") Dia.	120kg (264lb) *subject to fixing	Satin Chrome	1.5mm Metric
C212-3	3.0M (9' 10") LONG CABLE w/WALL SUPPORTS - Includes Spring Tensioner and 38mm (1-1/2") Dia. Conical Bases and Fixings	Cable Length: 3M (9' 10") Top Fixing: 16mm (5/8") Dia. Base Plate: 38MM (1-1/2") Dia.	60kg (132lb) *subject to fixing	Satin Chrome	1.5mm Metric
C213-3	3.0M (9' 10") LONG CABLE w/WALL SUPPORTS - Includes Spring Tensioner and 38mm (1-1/2") Dia. Bases and Fixings	Cable Length: 3M (9' 10") Top Fixing: 16mm (5/8") Dia. Base Plate: 38MM (1-1/2") Dia.	60kg (132lb) *subject to fixing	Satin Chrome	1.5mm Metric
BC4-2	ADDITIONAL METER CABLE -	4M (13' 1-1/2")	n/a	Galvanized Steel	n/a
BC5-2	2mm Dia. Galvanized Steel Cable cripped at one end	5M (16' 4")	n/a	Galvanized Steel	n/a

2mm Special Cable Fixings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
C205-4	4.0M (13' 1-1/2") LONG CABLE w/ ADJUSTABLE ANGLE CEILING TO FLOOR FITTINGS AND 38mm (1-1/2") Dia. BASE SUPPORTS - Includes Adjustable Angle Top (w/ Ball Bearing) and Bottom Fixings with Spring Tensioner	Cable Length: 4M (13' 1-1/2") Top & Bottom Fixing: 16mm (5/8") Dia. Base Plate: 38mm (1-1/2") Dia.	40kg (88lb) *subject to fixing	Satin Chrome	n/a
KC200-C2S	2.0 M (6' 6-3/4") LONG CABLE WITH CEILING FIXING AND SUPPORTS FOR HORIZONTAL PANELS OR SHELVES - Includes Cable and Ceiling Fixing w/Standard Base Support and C2S-02 Locking Support (*Require 14mm (35/64") Dia. Holes)	Cable Length: 2M (6' 6-3/4") Top Fixing: 16mm (5/8") Dia. Support: 20mm (3/4") Dia.	40kg (88lb) *subject to fixing	Satin Chrome	3/32" Standard
BC4-2	ADDITIONAL METER CABLE -	4M (13' 1-1/2")	n/a	Galvanized Steel	n/a
BC5-2	2mm Dia. Galvanized Steel Cable cripped at one end	5M (16' 4")	n/a	Galvanized Steel	n/a

Optional / Replacement Base Supports

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
CB-ST	STANDARD BASE SUPPORT - Optional / Replacement Base Support *Included with C100-2, C101-4, C200-2, C201-4 and C301-4 cable sets	12mm (1/2") Dia. 15mm (19/32") Depth	120kg (264lb) *subject to fixing	Satin Chrome	n/a
CB-25	25mm (1") Dia. BASE SUPPORT - Option / Replacement Base Support *Included with C202-4 cable set. Can also be used with any of the C100, C200, or C300 series cable sets	25mm (1") Dia. 19mm (3/4") Depth	120kg (264lb) *subject to fixing	Satin Chrome	n/a
CB-38-B	38mm (1-1/2") Dia. CONICAL BASE PLATE - Optional / Replacement Base Plate *Use with any of the C100, C200 or C300 series cable sets	38mm (1-1/2") Dia. 4mm (5/32") Depth	120kg (264lb) *subject to fixing	Satin Chrome	n/a
CB38-C	38mm (1-1/2") Dia. CONICAL BASE PLATE - Optional / Replacement Base Plate *Included with C112-3 and C212-3 cable sets. Can also be used with any of the C100, C200 or C300 series cable sets	38mm (1-1/2") Dia. 19mm (3/4") Depth	120kg (264lb) *subject to fixing	Satin Chrome	n/a
CB-38	38mm (1-1/2") Dia. BASE PLATE - Optional / Replacement Base Plate *Included with C113-3 and C203-4, C205-4, C213-3 cable sets. Can also be used with any of the C100, C200 or C300 series cable sets	38mm (1-1/2") Dia. 19mm (3/4") Depth	120kg (264lb) *subject to fixing	Satin Chrome	n/a
CB-50	50mm (2") Dia. HEAVY DUTY BASE SUPPORT - Optional / Replacement Base Support *Use with any of the C100, C200, of C300 series cable sets	50mm (2") Dia. 20mm (25/32") Depth	120kg (264lb) *subject to fixing	Satin Chrome	n/a

Single & Double Panel Supports

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
C2P-01	VERTICAL SUPPORT SINGLE - For panels up to 7mm (1/4") thick	16mm (5/8") Dia. 21mm (53/64") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard
C2P-02	VERTICAL SUPPORT SINGLE - For panels up to 7mm (1/4") thick	16mm (5/8") Dia. 33mm (1-19/64") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard
C2P-05	VERTICAL SUPPORT SINGLE - For panels up to 12.7mm (1/2") thick	21mm (53/64") Dia. 21mm (53/64") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard
C2P-03	SUPPORT FOR PANELS WITH HOLES SINGLE - For panels up to 6mm (1/4") thick or 10mm (3/8").	16mm (5/8") Dia. 25mm (1") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard
C2P-03 (3/8")	Includes Vinyl Washers. Hole size 6mm (15/64") Dia.	16mm (5/8") Dia. 25mm (1") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard

Single & Double Shelf Supports

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
C2S-03	CLAMP SUPPORT FOR GLASS SHELVES SINGLE - Up to 10mm (3/8") thick	18mm (45/64") Dia. 21mm (53/64") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard
C2S-04	CLAMP SUPPORT FOR GLASS SHELVES SINGLE - Up to 10mm (3/8") thick	18mm (45/64") Dia. 33mm (1-19/64") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard
C2S-05	CLAMP SUPPORT FOR GLASS SHELVES SINGLE - Up to 12.7mm (1/2") thick	21mm (53/64") Dia. 21mm (53/64") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard
C2S-01	SUPPORT FOR SHELF - Located under shelf. Shelf needs to be drilled or slotted. Hole Diameter: 10mm (3/8")	16mm (5/8") Dia. 14mm (35/64") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard
C2S-02	LOCKING/ADJUSTABLE SUPPORT FOR SHELF - To hold 6mm (15/64") as standard or up to 12.7mm (1/2") glass. Shelf needs to be drilled. Hole Diameter: 14mm (35/64")	20mm (3/4") Dia. 22mm (55/64") Depth	11.5kg (25lb) *subject to fixing	Satin Chrome	3/32" Standard

Frame Support & Sundry Fittings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
HRA400R/24		24" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
HRA400R/36	GRAPHIC HOLDER - Aluminum rails with clear plastic insert, end caps and P02 boss	36" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
HRA400R/42	Holds substrates up to 80 pt (3/32", 2mm) thick	42" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
HRA400R/48	Custom sizes available, please call for pricing (*CS03 cable supports not included)	48" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
HRA400R/60		60" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
HRAF100R/24	FABRIC HOLDER -	24" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
HRAF100R/36	Aluminum rails with plastic velcro/insert gripper set, end caps and P02 boss. Holds substrates up to 0.030" thick.	36" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
HRAF100R/42	Custom sizes available, please call for pricing (*CS03 cable supports not included)	42" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
HRAF100R/48		48" Length	11.5kg (25lb) *subject to fixing	Clear Anodized	n/a
C2F-21	SUPPORT-TOGGLE ASSEMBLY FOR ALUMINUM FRAME/SINGLE - For use with AnoFrame Round with 4mm (5/32") - 6mm (15/64") Channel Opening	16mm (5/8") Diameter 15.5mm (39/64") Length	11.5kg (25lb) *subject to fixing	Satin Chrome	1.5mm Metric & 3/32" Standard
C2F-22	SUPPORT-TOGGLE ASSEMBLY FOR ALUMINUM FRAME/DOUBLE - For use with AnoFrame Round with 4mm (5/32") - 6mm (15/64") Channel Opening	16mm (5/8") Diameter 22mm (55/64") Length	11.5kg (25lb) *subject to fixing	Satin Chrome	1.5mm Metric & 3/32" Standard
P02	BOSS FOR USE WITH SUPPORTS - Ref. CS03 or CS04 Use with up to no. 10 countersunk wood screw or bolt	12mm (15/32") Diameter 6mm (55/64") Depth	11.5kg (25lb) *subject to fixing	Nickel	n/a
C2F-25	PICTURE HOOK	16mm (5/8") Diameter 14mm (35/64") Length	11.5kg (25lb) *subject to fixing	Satin Chrome	1.5mm Metric & 3/32" Standard

Installation Accessories

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
MSB-25	WALL BRACKET SMALL - Fitted to the wall using up to no. 10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 25mm (63/64") from wall	30mm (1-3/16") Height 35mm (1-3/8") Depth	60kg (132lb) *subject to fixing	Silver	n/a
MSB	WALL BRACKET MEDIUM - Fitted to the wall using up to no. 10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 50mm (1-31/32") from wall	60mm (2-23/64") Height 60mm (2-23/64") Depth	45kg (99lb) *subject to fixing	Silver	n/a
MSB-100	WALL BRACKET LARGE - Fitted to the wall using up to no. 10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 100mm (3-15/16") from wall	110mm (4-21/64") Height 110mm (4-21/64") Depth	30kg (66lb) *subject to fixing	Silver	n/a
MDB	TRIANGULAR WALL BRACKET - Supplied with two nuts and bolts to connect rods to brackets Supports two rods 300mm (11-3/4") apart Hi-tech appearance. May be used as a cacanopt for a sign support.	350mm (1' 1-25/32") Height 350mm (1' 1-25/32") Depth	120kg (264lb) *subject to fixing	Silver	n/a
AC-4	REBATE CHANNEL - For rebating into, shelves, ect. For a flush finish.	1.2m (4')	n/a	Clear Anodized	n/a
AC-8	11.5mm (29/64") High; 19mm (7/8") Wide; 8.5mm (5/16") Opening	2.4m (8')	n/a	Clear Anodized	n/a
ACD-4	THRESHOLD CHANNEL - For floor mounting	1.2m (4')	n/a	Clear Anodized	n/a
ACD-8	8.6mm (5/16") High; 38mm (1-1/2") Wide; 8.5., (5/16") Opening	2.4m (8')	n/a	Clear Anodized	n/a
PH1035	DOUBLE SIDED CHANNEL - For wall mounting with MSB wall brackets and toggles 35mm (1-3/8") High; 19mm (3/4") Wide; 8.5mm (5/16") Opening	2.4m (8')	n/a	Clear Anodized	n/a
PH1005	DOUBLE SIDED CHANNEL - For wall mounting with MSB wall brackets and toggles 45.5mm (1-3/4") High; 19mm (3/4") Wide; 8.5mm (5/16") Opening	2.4m (8')	n/a	Clear Anodized	n/a
385 01	ALUMINUM & PLASTIC END CAPS - For PH Horizontal Extrusion Series	For PH1035	n/a	Clear Anodized	n/a
375 01		For PH1005	n/a	Clear Anodized	n/a
393		For PH1005	n/a	Gray Plastic	n/a
PC01-Q	QUICK FIT TOGGLE - Brass toggle that screws into the top end of a cable or wall fitting Unit fits directly into almost any make of channel	Screws into top end of cable or wall fitting	n/a	Brass	n/a
AT	TOGGLE - For fixing cables to channels. Can be used with all top and bottom fittings. Allen key provided.	3/8" long #10 screw	n/a	Unfinished	n/a
AT/L	Long version for use with isolators - order AT/L	1/2" long #10 screw	n/a	Unfinished	n/a
PA8	PA8 TOGGLE - For fixing cables to channels. Fits from the channel end. (*Also used for mounting channels onto the wall brackets)	25mm (1") Length, 12mm (1/2") Width	n/a	Unfinished	n/a
PA9	PA9 TOGGLE - For fixing cables to channels. Fits from the channel opening.	25mm (1") Length, 10mm (7/16") Width	n/a	Unfinished	n/a