

3.0mm Rod Fixings Components

3mm Basic Rod Fixings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
RB1	1.0M (3' 3-3/8") LONG ROD WITH ADJUSTABLE ANGLE FIXING - Screw Fixing Type for Ceiling or Wall Ideal for supporting signs & graphic panels	Rod Length: 1.0M (3' 3-3/8") Top Fixing: 16mm (5/8") Dia.	120kg (264lb) *Subject to fixing	Satin Chrome	n/a
RB2	2.0M (6' 6-3/4") LONG ROD WITH ADJUSTABLE ANGLE FIXING - Screw Fixing Type for Ceiling or Wall Ideal for supporting signs & graphic panels	Rod Length: 2.0M (6' 6-3/4") Top Fixing: 16mm (5/8") Dia.	120kg (264lb) *Subject to fixing	Satin Chrome	n/a
RBT1	1.0M (3' 3-3/8") LONG ROD w/ADJUSTABLE ANGLE FIXING & PA8 TOGGLE - For Fixing to Channel	Rod Length: 1.0M (3' 3-3/8") Top Fixing: 16mm (5/8") Dia.	120kg (264lb) *Subject to fixing	Satin Chrome	n/a
RBT2	2.0M (6' 6-3/4") LONG ROD w/ADJUSTABLE ANGLE FIXING & PA8 TOGGLE - For Fixing to Channel	Rod Length: 2.0M (6' 6-3/4") Top Fixing: 16mm (5/8") Dia.	120kg (264lb) *Subject to fixing	Satin Chrome	n/a
KRB1-CG05-3	TOP ROD FIXING AND PANEL CLAMP - 1.0M (3' 3-3/8") Long Rod with Adjustable Angle Fixing for Ceiling or Wall and Support for 1/4" Thick Panels Ideal for supporting signs & graphic panels from top	Rod Length: 1.0M (3' 3-3/8") Top Fixing & Panel Support: 16mm (5/8") Dia.	40kg (88lb) *Subject to fixing	Satin Chrome	1.5mm & 3mm Metric

3mm Special Rod Fixings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
R1200-3	1.2M (3' 11-1/4") LONG ROD WITH RETURN - To be used with suction cups. Ideal for supporting window displays	Rod Length: 1.2M (3' 11-1/4")	10kg (22lb) *Subject to fixing	Satin Chrome	n/a
REC-P-3/BL	*Include one end cap REC-P-3/BL		n/a	Black Plastic	n/a
RC-6505-00	CLEAR SUCTION CUP WITH 5/32" SIDE-PILOT - For mounting R1200-3 rods to any window surface. *Use 1-2 suction cups per rod. Installation Notes: moisten the back side and press firmly to the surface until you hear a pop	2" Dia. Suction Cup Light-weight applications only	10kg (22lb) *Subject to fixing	Clear Plastic	n/a
R1200-3/RC1	SUCTION CUP / 1.2M (3' 11-1/4") LONG ROD SET - Supplied with one R1200-3 rod and one RC-6505-00 suction cup *Use with CG03-3 or CG04-3 panel supports	Rod Length: 1.2M (3' 11-1/4") 2" Dia. Suction Cup	10kg (22lb) *Subject to fixing	Stainless Steel/Clear Plastic	n/a
R1200-3/RC2	SUCTION CUP / 1.2M (3' 11-1/4") LONG ROD SET - Supplied with one R1200-3 rod and two RC-6505-00 suction cups *Use with CG03-3 or C.G04-3 panel supports	Rod Length: 1.2M (3' 11-1/4") 2" Dia. Suction Cup	10kg (22lb) *Subject to fixing	Stainless Steel/Clear Plastic	n/a

Single & Double Panel Supports

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
CG05-3	TOP PANEL SUPPORT - For panels up to 7mm (1/4") thick Ideal for supporting signs & graphic panels from top	16mm (5/8") Diameter 21mm (53/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm & 3.0mm Metric
CG03-3	VERTICAL SUPPORT SINGLE - For panels up to 4mm (5/32") thick	10mm (25/64") Diameter 15mm (19/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm & 3.0mm Metric
CG04-3	VERTICAL SUPPORT DOUBLE - For panels up to 4mm (5/32") thick	10mm (25/64") Diameter 22mm (55/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm & 3.0mm Metric
CG01-3	VERTICAL SUPPORT SINGLE - For panels up to 7mm (1/4") thick	16mm (5/8") Diameter 21mm (53/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm & 3.0mm Metric
CG14-3	VERTICAL SUPPORT SINGLE - For panels up to 12.7mm (1/2") thick	20.5mm (13/16") Diameter 21mm (53/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm & 3.0mm Metric
CG11-3	MULTI-POSITION PANEL SUPPORT SINGLE - For panels up to 7mm (1/4") thick Adjustable to any angle. Can be locked into position.	16mm (5/8") Diameter 28mm (1-7/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG21-3	MULTI-POSITION PANEL SUPPORT DOUBLE - For panels up to 7mm (1/4") thick Adjustable to any angle. Can be locked into position.	16mm (5/8") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG13-3	MULTI-POSITION PANEL SUPPORT SINGLE - For panels up to 10mm (3/8") thick. Adjustable to any angle. Can be locked into position.	18mm (45/64") Diameter 28mm (1-7/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG23-3	MULTI-POSITION PANEL SUPPORT DOUBLE - For panels up to 10mm (3/8") thick Adjustable to any angle. Can be locked into position.	18mm (45/64") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG12-3	TOP/BOTTOM MULTI POSITION SUPPORT SINGLE - For panels wider than the distance between cables Panels up to 7mm (1/4") thick Adjustable for any angle. Can be locked into position.	16mm (5/8") Diameter 31mm (1-7/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG22-3	TOP/BOTTOM MULTI POSITION SUPPORT DOUBLE - For panels wider than the distance between cables Panels up to 7mm (1/4") thick Adjustable for any angle. Can be locked into position.	16mm (5/8") Diameter 52mm (2-3/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CS13-3	SUPPORT FOR PANELS WITH HOLES SINGLE - For panels up to 5/6mm thick. Hole size 6mm (15/64") Dia. (***Supports for panels up to 20mm (25/32") thick are also available. Please Call)	16mm (5/8") Diameter 24.5mm (31/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.0mm & 3.0 mm Metric
CS23-3	SUPPORT FOR PANELS WITH HOLES DOUBLE - For panels up to 5/6mm thick. Hole size 6mm (15/64") Dia. (***Supports for panels up to 20mm (25/32") thick are also available. Please Call)	16mm (5/8") Diameter 38.5mm (1-33/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.0mm & 3.0 mm Metric
CS03-3	SUPPORT SINGLE - For any item fitted with boss ref. PO2 12mm (15/32") Internal Diameter; 6mm (15/64") Internal Depth	16mm (5/8") Diameter 14mm (35/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 3.0mm Metric
P02	BOSS FOR USE WITH SUPPORTS - Ref. CS03 or CS04 Use with up to no. 10 countersunk wood screw or bolt	12mm (15/32") Diameter 6mm (15/64") Depth	n/a	Nickel	n/a

Single & Double Shelf Supports

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
CG11-3	MULTI-POSITION PANEL SUPPORT SINGLE - For panels up to 7mm (1/4") thick Adjustable to any angle. Can be locked into position.	16mm (5/8") Diameter 28mm (1-7/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG21-3	MULTI-POSITION PANEL SUPPORT DOUBLE - For panels up to 7mm (1/4") thick Adjustable to any angle. Can be locked into position.	16mm (5/8") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG13-3	MULTI-POSITION PANEL SUPPORT SINGLE - For panels up to 10mm (3/8") thick Adjustable to any angle. Can be locked into position.	18mm (45/64") Diameter 28mm (1-7/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG23-3	MULTI-POSITION PANEL SUPPORT DOUBLE - For panels up to 10mm (3/8") thick Adjustable to any angle. Can be locked into position.	18mm (45/64") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.5mm & 3.0mm Metric
CG15-3	CLAMP SUPPORT FOR GLASS SHELVES SINGLE - Up to 12.7mm (1/2") thick.	20.5mm (13/16") Diameter 21mm (53/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	3.0mm Metric
CS01-3	SUPPORT FOR SHELF - Located under shelf. Shelf is drilled and slotted.	16mm (5/8") Diameter 8mm (5/16") Depth	11.5kg (25lb) *Subject to fixing	Satin Chrome	3.0mm Metric
CS11-3	SUPPORT FOR WOODEN SHELF OR GLASS SHELVES SINGLE - Adjustable to any angle or slope Can be locked into position. For glass shelves add ref. P08.	16mm (5/8") Diameter 37mm (1-29/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	3.0mm Metric
CS21-3	SUPPORT FOR WOODEN SHELF OR GLASS SHELVES DOUBLE - Adjustable to any angle or slope Can be locked into position. For glass shelves add ref. P08.	16mm (5/8") Diameter 64mm (2-33/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	3.0mm Metric
P08	SCREW TO RETAIN GLASS SHELVES - Supported on CS11-3 or CS21-3 to hold 6mm (15/64") thick as standard. Flush finish. Plastic insert to project glass. 16mm (5/8") Dia.	Hole 6mm (15/64") Dia. 12mm (15/32") from edge of glass	n/a	Satin Chrome	n/a

Frame Supports & Sundry Fittings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
HRAG400R/24	GRAPHIC HOLDER - Aluminum rails with clear plastic insert, end caps and P02 boss Holds substrates up to 80 pt (3/32", 2 mm) thick Custom sizes available, please call for pricing. (*CS03 cable supports not included)	24" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAG400R/36		36" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAG400R/42		42" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAG400R/48		48" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAG400R/60		60" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/24	FABRIC HOLDER - Aluminum rails with plastic velcro/insert gripper set, end caps and P02 boss Holds substrates up to 0.030" thick Custom sizes available, please call for pricing. (*CS03 cable supports not included)	24" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/36		36" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/42		42" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/48		48" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/60		60" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
BR19C3-3/PC	BANNER RAIL - Polished chrome rails, supplied with CS03-3 & P02 supports to fit directly onto cables, no additional fittings required.	19mm (3/4") Diameter 3 & 4 Feet Length	11.5kg (25lb) *Subject to fixing	Polished Chrome	n/a
BR19C3-4/PC		19mm (3/4") Diameter 3 & 4 Feet Length	11.5kg (25lb) *Subject to fixing	Polished Chrome	n/a
HR25C3-3/PC	HANGING RAIL - Heavy Duty. Ideal for garments. Polished chrome rails, supplied with CS03-3 & P02 support to fit directly onto cables, no additional fittings required	25mm (1") Diameter 3 & 4 Feet Length	11.5kg (25lb) *Subject to fixing	Polished Chrome	n/a
HR25C3-4/PC		25mm (1") Diameter 3 & 4 Feet Length	11.5kg (25lb) *Subject to fixing	Polished Chrome	n/a
CS12-3	Picture Hook	16mm (5/8") Diameter 30mm (1-3/16") Height	11.5kg (25lb) *Subject to fixing	Satin Chrome	3.0mm Metric
KCS03-3/CT01	SUPPORT-TOGGLE ASSEMBLY FOR ALUMINUM FRAME / SINGLE - For use with AnoFrame Round with 4mm (5/32") - 6mm (15/64") Channel Opening.	16mm (5/8") Diameter 14mm (35/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm Metric & 3/32" Standard
CS03-3	SUPPORT SINGLE - For any item fitted with boss ref. PO2. 12mm (15/32") Internal Diameter; 6mm (15/64") Internal Depth.	16mm (5/8") Diameter 14mm (35/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	3.0mm Metric
P02	BOSS FOR USE WITH SUPPORTS - Ref. CS03 or CS04. Use with up to no. 10 countersunk wood screw or bolt.	12mm (15/32") Diameter 6mm (15/64") Depth	n/a	Nickel	n/a
CS05-3	SUPPORT SINGLE - For 6mm (1/4") Dia. Rod	16mm (5/8") Diameter 14mm (35/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm Metric & 3/32" Standard
RR01-3/6	MULTI-POSITION ROD TO ROD SUPPORT - Holds one 3mm and one 6mm rods at any angle. Can be locked into position.	16mm (5/8") Diameter 31mm (1-7/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm, 2.0mm, & 3.0mm Metric
R1000P	LONG UNTHREADED ROD - 1.0M (3' 3-3/8") LONG ROD UNTHREADED. (*To be used with CS05-3 supports in horizontal applications).	6mm (15/64") Dia. Rod 1.0M (3' 3-3/8") Length	n/a	Stainless Steel	n/a

Installation Accessories

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
MSB-25	WALL BRACKET SMALL - Fitted to the wall using up to no. 10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 25mm (63/64") from wall	30mm (1-3/16") Height 35mm (1-3/8") Depth	60kg (132lb) *Subject to fixing	Silver	n/a
MSB	WALL BRACKET MEDIUM - Fitted to the wall using up to no. 10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 50mm (1-31/32") from wall	60mm (2-23/64") Height 60mm (2-23/64") Depth	45kg (99lb) *Subject to fixing	Silver	n/a
MSB-100	WALL BRACKET LARGE - Fitted to the wall using up to no.10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 100mm (3-15/16") from wall	110mm (4-21/64") Height 110mm (4-21/64") Depth	30kg (66lb) *Subject to fixing	Silver	n/a
MDB	TRIANGULAR WALL BRACKET - Supplied with two nuts and bolts to connect rods to brackets Supports two rods 300mm (11-3/4") apart Hi-tech appearance. Can be used as a canopy of a sign support.	350mm (1' 1-25/32") Height 350mm (1' 1-25/32") Depth	120kg (264lb) *Subject to fixing	Silver	n/a
AC-4	REBATE CHANNEL - For rebating into, shelves, etc. For a flush finish.	1.2m (4 ft)	n/a	Clear Anodized	n/a
AC-8	11.5mm (29/64") High; 19mm (7/8") Wide; 8.5mm (5/16") Opening	2.4m (8ft)	n/a	Clear Anodized	n/a
ACD-4	THRESHOLD CHANNEL - For floor mounting. 8.6mm (5/16") High; 38mm (1-1/2") Wide; 8.5mm (5/16") Opening.	1.2m (4 ft)	n/a	Clear Anodized	n/a
ACD-8		2.4m (8ft)	n/a	Clear Anodized	n/a
PH1035	DOUBLE SIDED CHANNEL - For wall mounting with MSB wall brackets and toggles. 35mm (1-3/8") High; 19mm (3/4") Wide; 8.5mm (5/16") Opening	2.4m (8 FT)	n/a	Clear Anodized	n/a
PH1005	DOUBLE SIDED CHANNEL - For wall mounting with MSB wall brackets and toggles 45.5mm (1-3/4") High; 19mm (3/4") Wide; 8.5mm (5/16") Opening	2.4m (8 FT)	n/a	Clear Anodized	n/a
385 01		For PH1035	n/a	Clear Anodized	n/a
375 01	ALUMINUM & PLASTIC END CAPS - For PH Horizontal Extrusion Series	For PH1005	n/a	Clear Anodized	n/a
393		For PH1005	n/a	Gray Plastic	n/a
AT	TOGGLE - For fixing cables to channels. Can be used with all top and bottom fittings.	3/8" long #10 screw	120kg (264lb) *Subject to fixing	Unfinished	n/a
AT/L	Allen key provided. Long version for use with isolators - order AT/L	1/2" long #10 screw	120kg (264lb) *Subject to fixing	Unfinished	n/a
PA8	PA8 TOGGLE - For fixing cables to channels. Fits from the channel end. (*Also used for mounting channels onto the wall brackets).	25mm (1") Length 12mm (1/2") Width	120kg (264lb) *Subject to fixing	Unfinished	n/a

PA9	PA9 TOGGLE - For fixing cables to channels Fits directly onto channel opening	25mm (1") Length 10mm (7/16") Width	120kg (264lb) *Subject to fixing	Unfinished	n/a
CS08-3	POWER CONNECTOR - Allows electrical power to be connected to the cable Excellent connection	12mm (15/32") Diameter 12mm (15/32") Length	n/a	Satin Chrome	1.5mm & 2.5mm Metric
PC01/I	TOP ISOLATOR - Black nylon for cables	n/a	n/a	Black	n/a
SP/IS	BOTTOM ISOLATOR - Three sections in white nylon	n/a	n/a	White	n/a
P01	DECORATIVE SUPPORT PLATE Add to any of the cable / rod systems fittings	38mm (1-1/2") Diameter	n/a	Satin Chrome	n/a