

6.0mm Rod Fixings Components

6mm Basic Rod Fixings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
RAS	TOP/BOTTOM FIXINGS FOR ROD - Includes Spring Tensioner, top/ceiling and bottom/floor fixings	18mm (45/64") Diameter top and bottom fixings	200kg (440lb) *Subject to fixing	Satin Chrome	1.5mm Metric
RS	ROD CEILING SUPPORT - Screw fit	18mm (45/64") Diameter	200kg (440lb) *Subject to fixing	Satin Chrome	n/a
RP	ROD SUPPORT - Push fit with grub screw *** Not recommended for ceiling mounted applications	18mm (45/64") Diameter	11.5kg (25lb) *Subject to Fixing	Satin Chrome	1.5mm Metric
R1500	LONG THREADED ROD - 1.5M (4' 11-1/16") Long Rod Threaded at Both Ends	6mm (15/64") Dia. Rod 1.5M (4' 11-1/16") Length	n/a	Brushed Stainless	n/a
R500	SHORT THREADED ROD - 0.5M (1' 7-11/16") Long Rod Threaded at One End - Other End Domed	6mm (15/64") Dia. Rod 0.5M (1' 7-11/16") Length	n/a	Brushed Stainless	n/a
R1000P	LONG UNTHREADED ROD - 1.0M (3' 3-3/8") Long Rod Unthreaded	6mm (15/64") Dia. Rod 1.0M (3' 3-3/8") Length	n/a	Brushed Stainless	n/a
R500P	SHORT UNTHREADED ROD - 0.5M (1' 7-11/16") Long Rod Unthreaded	6mm (15/64") Dia. Rod 0.5M (1' 7-11/16") Length	n/a	Brushed Stainless	n/a

6mm Special Rod Fixings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
RAAS	ANGLED TOP FIXING WITH BOTTOM FLOOR SUPPORT - Adjustable through 180°, the top fitting can be fixed to sloping ceiling, flat ceiling or wall	18mm (45/64") Diameter top and bottom fixings	50kg (110lb) *Subject to fixing	Satin Chrome	1.5mm & 3.0mm Metric
RSA	ANGLED SUPPORT - Screw fit	15mm (19/32") Diameter	50kg (110lb) *Subject to fixing	Satin Chrome	3.0mm Metric
RPA	ANGLED SUPPORT - Push fit with grub screw	15mm (19/32") Diameter	11.5kg (25lb) *Subject to Fixing	Satin Chrome	1.5mm & 3.0mm Metric
WM11	WALL FIXING FOR 6mm (15/64") ROD - Locks at any angle	16mm (5/8") Diameter 31mm (1-7/32") Length	11.5kg (25lb) *Subject to Fixing	Satin Chrome	1.5mm Metric
HDS-WM11	HEAVY DUTY SUPPORT & ROD FIXING SET - Supplied with three 1-1/2" long wood screws	50mm (2") Diameter 36mm (1-1/2") Length	22.5kg (50lb) *Subject to Fixing	Satin Chrome	1.5mm & 2.5mm Metric
RS03	SUPPORT - SINGLE - For any item fitted with boss ref. PO2 12mm (15/32") Internal Diameter; 6mm (15/64") Internal Depth	16mm (5/8") Diameter 18mm (45/64") Length	11.5kg (25lb) *Subject to Fixing	Satin Chrome	1.5mm & 2.5mm Metric
P02	BOSS FOR USE WITH SUPPORTS - Ref. RS03 or RS04 Use with up to no. 10 countersunk wood screw or bolt	12mm (15/32") Diameter 6mm (15/64") Depth	n/a	Nickel	n/a
RP	ROD SUPPORT - Push fit with grub screw Customized Depth - fix rods back to the wall using RP, custom cut rod length and RS05	16mm (5/8") Diameter 21mm (53/64") Length	11.5kg (25lb) *Subject to Fixing	Satin Chrome	1.5mm Metric
RS05	ROD SUPPORT - SINGLE - For 6mm (15/64") Dia. Rod Customized Depth - fix rods back to the wall using RP, custom cut rod length and RS05	16mm (5/8") Diameter 17mm (43/64") Length	11.5kg (25lb) *Subject to Fixing	Satin Chrome	1.5mm & 2.5mm Metric
P01	DECORATIVE SUPPORT PLATE - Add to any of the cable / rod systems fittings	38mm (1-1/2") Diameter	n/a	Satin Chrome	n/a

Single and Double Panel Supports

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
RG05	SIGN SUPPORT - For panels up to 7mm (1/4") thick Supports sign from above	16mm (5/8") Diameter 16mm (5/8") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG01	VERTICAL SUPPORT SINGLE - For panels up to 7mm (1/4") thick	16mm (5/8") Diameter 25mm (63/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RG02	VERTICAL SUPPORT DOUBLE - For panels up to 7mm (1/4") thick	16mm (5/8") Diameter 36mm (1-27/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RGN01	SIGN SUPPORT NON REMOVABLE - For panels up to 7mm (1/4") thick Supports signs from the side	16mm (5/8") Diameter 23mm (29/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RG14	VERTICAL SUPPORT SINGLE - For panels up to 12.7mm (1/2") thick	20mm (13/16") Diameter 29mm (1-1/8") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG11	MULTI-POSITION PANEL SUPPORT SINGLE - For panels up to 7mm (1/4") thick Adjustable to any angle. Can be locked into position.	16mm (5/8") Diameter 30mm (1-3/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG21	MULTI-POSITION PANEL SUPPORT DOUBLE - For panels up to 7mm (1/4") thick Adjustable to any angle. Can be locked into position.	16mm (5/8") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG13	MULTI-POSITION PANEL SUPPORT SINGLE - For panels up to 10mm (3/8") thick Adjustable to any angle. Can be locked into position.	18mm (45/64") Diameter 30mm (1-3/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG23	MULTI-POSITION PANEL SUPPORT DOUBLE - For panels up to 10mm (3/8") thick Adjustable to any angle. Can be locked into position.	18mm (45/64") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG12	TOP/BOTTOM MULTI POSITION SUPPORT SINGLE - For panels wider than the distance between rods Panels up to 7mm (1/4") thick Adjustable for any angle. Can be locked into position.	16mm (5/8") Diameter 33mm (1-17/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG22	TOP/BOTTOM MULTI POSITION SUPPORT DOUBLE - For panels wider than the distance between rods Panels up to 7mm (1/4") thick Adjustable for any angle. Can be locked into position.	16mm (5/8") Diameter 52mm (2-3/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RS13	SUPPORT FOR PANELS WITH HOLES SINGLE - For panels up to 5/6mm thick Hole size 6mm (15/64") Dia. *Supports for panels up to 20mm (25/32") thick are also available	16mm (5/8") Diameter 27mm (1-1/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RS23	SUPPORT FOR PANELS WITH HOLES DOUBLE - For panels up to 5/6mm thick Hole size 6mm (15/64") Dia. *Supports for panels up to 20mm (25/32") thick are also available	16mm (5/8") Diameter 42mm (1-21/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RS03	SUPPORT SINGLE - For any item fitted with boss ref. PO2 12mm (15/32") Internal Diameter; 6mm (15/64") Internal Depth	16mm (5/8") Diameter 18mm (45/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RS04	SUPPORT DOUBLE - For any item fitted with boss ref. PO2 12mm (15/32") Internal Diameter; 6mm (15/64") Internal Depth	16mm (5/8") Diameter 21mm (53/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
P02	BOSS FOR USE WITH SUPPORTS - Ref. RS03 or RS04 Use with up to no. 10 countersunk wood screw or bolt	12mm (15/32") Diameter 6mm (15/64") Depth	n/a	Nickel	n/a

Single and Double Shelf Supports

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
RG06	CLAMP SUPPORT FOR GLASS SHELVES SINGLE - Up to 7mm (1/4") thick	16mm (5/8") Diameter 25mm (63/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RG07	CLAMP SUPPORT FOR GLASS SHELVES DOUBLE - Up to 7mm (1/4") thick	16mm (5/8") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RG15	CLAMP SUPPORT FOR GLASS SHELVES SINGLE - Up to 12.7mm (1/2") thick	20mm (13/16") Diameter 29mm (1-1/8") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RG11	MULTI-POSITION PANEL SUPPORT SINGLE - For panels up to 7mm (1/4") thick Adjustable to any angle. Can be locked into position.	16mm (5/8") Diameter 30mm (1-3/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG21	MULTI-POSITION PANEL SUPPORT DOUBLE - For panels up to 7mm (1/4") thick Adjustable to any angle. Can be locked into position.	16mm (5/8") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG13	MULTI-POSITION PANEL SUPPORT SINGLE - For panels up to 10mm (3/8") thick Adjustable to any angle. Can be locked into position.	18mm (45/64") Diameter 30mm (1-3/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RG23	MULTI-POSITION PANEL SUPPORT DOUBLE - For panels up to 10mm (3/8") thick Adjustable to any angle. Can be locked into position.	18mm (45/64") Diameter 46mm (1-13/16") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RS01	SUPPORT FOR SHELF - Locates under shelf. Shelf requires 10mm (3/8") Dia. Hole Non removable support	16mm (5/8") Diameter	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RS11	SUPPORT FOR WOODEN SHELF OR GLASS SHELVES SINGLE - Adjustable to any angle of slope Can be locked into position For glass shelves add ref. P08	8mm (5/16") Depth	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RS21	SUPPORT FOR WOODEN SHELF OR GLASS SHELVES DOUBLE - Adjustable to any angle of slope Can be locked into position For glass shelves add ref. P08	16mm (5/8") Diameter	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
P08	SCREW TO RETAIN GLASS SHELVES - Supported on RS11 or RS21 to hold 6mm (15/64") thick as standard Flush finish Plastic insert to project glass 16mm (5/8") Dia	Hole 6mm (15/64") Dia. 12mm (15/32") from edge of glass	n/a	Satin Chrome	n/a

Frame Supports & Sundry Fittings

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
HRAG400R/24		24" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAG400R/36	GRAPHIC HOLDER - Aluminum rails with clear plastic insert, end caps and P02 boss	36" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAG400R/42	Holds substrates up to 80 pt (3/32", 2 mm) thick Custom sizes available, please call for pricing	42" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAG400R/48	(*CS03 cable supports not included)	48" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAG400R/60		60" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/24		24" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/36	FABRIC HOLDER - Aluminum rails with plastic velcro/insert gripper set, end caps and P02 boss	36" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/42	Holds substrates up to 0.030" thick Custom sizes available, please call for pricing	42" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/48	(*CS03 cable supports not included)	48" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
HRAFH100R/60		60" Length	11.5kg (25lb) *Subject to fixing	Clear Anodized	n/a
BR19C3-3/PC	BANNER RAIL - Polished chrome rails, supplied with CS03-3 & P02 supports to fit directly onto cables, no additional fittings required	19mm (3/4") Diameter 3 & 4 Feet Length	11.5kg (25lb) *Subject to fixing	Polished Chrome	n/a
BR19C3-4/PC		19mm (3/4") Diameter 3 & 4 Feet Length	11.5kg (25lb) *Subject to fixing	Polished Chrome	n/a
HR25C3-3/PC	HANGING RAIL - Heavy Duty Ideal for garments	25mm (1") Diameter 3 & 4 Feet Length	11.5kg (25lb) *Subject to fixing	Polished Chrome	n/a
HR25C3-4/PC	Polished chrome rails, supplied with CS03-3 & P02 supports to fit directly onto cables, no additional fittings required	25mm (1") Diameter 3 & 4 Feet Length	11.5kg (25lb) *Subject to fixing	Polished Chrome	n/a
RS12	PICTURE HOOK	16mm (5/8") Diameter 30mm (1-3/16") Height	11.5kg (25lb) *Subject to fixing	Satin Chrome	2.5mm Metric
RS03	SUPPORT SINGLE - For any item fitted with boss ref. PO2 12mm (15/32") Internal Diameter; 6mm (15/64") Internal Depth	16mm (5/8") Diameter 18mm (45/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RS04	SUPPORT DOUBLE - For any item fitted with boss ref. PO2 12mm (15/32") Internal Diameter; 6mm (15/64") Internal Depth	16mm (5/8") Diameter 21mm (53/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
P02	BOSS FOR USE WITH SUPPORTS - Ref. RS03 or RS04 Use with up to no. 10 countersunk wood screw or bolt	12mm (15/32") Diameter 6mm (15/64") Depth	n/a	Nickel	n/a
RS05	SUPPORT SINGLE - For 6mm (1/4") Dia. Rod	16mm (5/8") Diameter 17mm (43/64") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RS06	SUPPORT DOUBLE - For 6mm (1/4") Dia. Rod	16mm (5/8") Diameter 20mm (25/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RR01	MULTI-POSITION ROD SUPPORT - For 6mm (1/4") Dia Rod at any angle. Can be locked into position.	16mm (5/8") Diameter 31mm (1-7/32") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.5mm Metric
RR01-6/10	MULTI-POSITION ROD SUPPORT - Holds one 6mm and one 10mm Rods at any angle. Can be locked into position.	18mm (11/16") Diameter 35mm (1-3/8") Length	11.5kg (25lb) *Subject to fixing	Satin Chrome	1.5mm & 2.0mm Metric
REC	DECORATIVE END CUP - For 1/4" Dia. Rod	21mm (53/64") Diameter 31mm (1-7/32") Length	n/a	Satin Chrome	1.5mm Metric

Installation Accessories

Item Number	Description	Dimensions	Load Limits	Finish	Allen Wrench
MSB-25	WALL BRACKET SMALL - Fitted to the wall using up to no. 10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 25mm (63/64") from wall	30mm (1-3/16") Height 35mm (1-3/8") Depth	60kg (132lb) *Subject to fixing	Silver	n/a
MSB	WALL BRACKET MEDIUM - Fitted to the wall using up to no. 10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 50mm (1-31/32") from wall	60mm (2-23/64") Height 60mm (2-23/64") Depth	45kg (99lb) *Subject to fixing	Silver	n/a
MSB-100	WALL BRACKET LARGE - Fitted to the wall using up to no. 10 screws Supplied with nut and bolt to connect cable to bracket Cable/Rod Fixing: 100mm (3-15/16") from wall	110mm (4-21/64") Height 110mm (4-21/64") Depth	30kg (66lb) *Subject to fixing	Silver	n/a
MDB	TRIANGULAR WALL BRACKET - Supplied with two nuts and bolts to connect rods to brackets Supports two rods 300mm (11-3/4") apart Hi-tech appearance. Can be used as a canopy of a sign support.	350mm (1' 1-25/32") Height 350mm (1' 1-25/32") Depth	120kg (264lb) *Subject to fixing	Silver	n/a
AC-4	REBATE CHANNEL - For rebating into, shelves, etc.	1.2m (4 ft)	n/a	Clear Anodized	n/a
AC-8	For a flush finish 11.5mm (29/64") High; 19mm (7/8") Wide; 8.5mm (5/16") Opening	2.4m (8ft)	n/a	Clear Anodized	n/a
ACD-4	THRESHOLD CHANNEL - For floor mounting. 8.6mm	1.2m (4 ft)	n/a	Clear Anodized	n/a
ACD-8	(5/16") High; 38mm (1-1/2") Wide; 8.5mm (5/16") Opening	2.4m (8ft)	n/a	Clear Anodized	n/a
PH1035	DOUBLE SIDED CHANNEL - For wall mounting with MSB wall brackets and toggles 35mm (1-3/8") High; 19mm (3/4") Wide; 8.5mm (5/16") Opening	2.4m (8 FT)	n/a	Clear Anodized	n/a
PH1005	DOUBLE SIDED CHANNEL - For wall mounting with MSB wall brackets and toggles 45.5mm (1-3/4") High; 19mm (3/4") Wide; 8.5mm (5/16") Opening	2.4m (8 FT)	n/a	Clear Anodized	n/a
385 01		For PH1035	n/a	Clear Anodized	n/a
375 01	ALUMINUM & PLASTIC END CAPS - For PH Horizontal Extrusion Series	For PH1005	n/a	Clear Anodized	n/a
393		For PH1005	n/a	Gray Plastic	n/a
PR01-Q	QUICK FIT TOGGLE - Brass toggle that screws into the top end of a rod or wall fitting	Unit fits directly into almost any make of channel	* Not recommended for heavy loads	Brass	n/a
AT	TOGGLE - For fixing cables to channels Can be used with all top and bottom fittings	3/8" long #10 screw	120kg (264lb) *Subject to fixing	Unfinished	n/a
AT/L	Allen key provided Long version for use with isolators - order AT/L	1/2" long #10 screw	120kg (264lb) *Subject to fixing	Unfinished	n/a
PA8	PA8 TOGGLE - For fixing cables to channels Fits from the channel end (*Also used for mounting channels onto the wall brackets)	25mm (1") Length 12mm (1/2") Width	120kg (264lb) *Subject to fixing	Unfinished	n/a
PA9	PA9 TOGGLE - For fixing cables to channels Fits directly onto channel opening	25mm (1") Length 10mm (7/16") Width	120kg (264lb) *Subject to fixing	Unfinished	n/a
RS08	POWER CONNECTOR - Allows electrical power to be connected to the rod Excellent connection	12mm (15/32") Diameter 12mm (15/32") Length	n/a	Satin Chrome	1.5mm & 2.5mm Metric

PC01/I	TOP ISOLATOR - Black nylon for cables.	n/a	n/a	Black	n/a
SP/IS	BOTTOM ISOLATOR - Three sections in white nylon	n/a	n/a	White	n/a
P01	DECORATIVE SUPPORT PLATE - Add to any of the cable / rod systems fittings	38mm (1-1/2") Diameter	n/a	Satin Chrome	n/a