

## Aluminum Standoff Supports - Specifications

Item Code No.	Item Dimensions	Panel Thickness	Panel Hole Dia.	Cap Type	Coupling Anchor Type	Mounting Screw No.	Finish Type
<b>WSO15-3/4 AL</b>	5/8" Dia. x 3/4" L	1/4" max	1/4"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1 AL</b>	5/8" Dia. x 1" L	1/4" max	1/4"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1-1/4 AL</b>	5/8" Dia. x 1-1/4" L	1/4" max	1/4"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1-1/2 AL</b>	5/8" Dia. x 1-1/2" L	1/4" max	1/4"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-3/4 AL/R</b>	5/8" Dia. x 3/4" L	1/4" max	1/4"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1 AL/R</b>	5/8" Dia. x 1" L	1/4" max	1/4"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1-1/4 AL/R</b>	5/8" Dia. x 1-1/4" L	1/4" max	1/4"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1-1/2 AL/R</b>	5/8" Dia. x 1-1/2" L	1/4" max	1/4"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-3/4 AL/H</b>	5/8" Dia. x 3/4" L	1/4" max	1/4"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1 AL/H</b>	5/8" Dia. x 1" L	1/4" max	1/4"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1-1/4 AL/H</b>	5/8" Dia. x 1-1/4" L	1/4" max	1/4"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO15-1-1/2 AL/H</b>	5/8" Dia. x 1-1/2" L	1/4" max	1/4"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-3/4 AL</b>	3/4" Dia. x 3/4" L	5/16" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1 AL</b>	3/4" Dia. x 1" L	5/16" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1-1/4 AL</b>	3/4" Dia. x 1-1/4" L	5/16" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1-1/2 AL</b>	3/4" Dia. x 1-1/2" L	5/16" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-3/4 AL/R</b>	3/4" Dia. x 3/4" L	5/16" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1 AL/R</b>	3/4" Dia. x 1" L	5/16" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1-1/4 AL/R</b>	3/4" Dia. x 1-1/4" L	5/16" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1-1/2 AL/R</b>	3/4" Dia. x 1-1/2" L	5/16" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-3/4 AL/L</b>	3/4" Dia. x 3/4" L	5/16" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1 AL/L</b>	3/4" Dia. x 1" L	5/16" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1-1/4 AL/L</b>	3/4" Dia. x 1-1/4" L	5/16" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1-1/2 AL/L</b>	3/4" Dia. x 1-1/2" L	5/16" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-3/4 AL/H</b>	3/4" Dia. x 3/4" L	5/16" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1 AL/H</b>	3/4" Dia. x 1" L	5/16" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1-1/4 AL/H</b>	3/4" Dia. x 1-1/4" L	5/16" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO20-1-1/2 AL/H</b>	3/4" Dia. x 1-1/2" L	5/16" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized

## Aluminum Standoff Supports - Specifications

Item Code No.	Item Dimensions	Panel Thickness	Panel Hole Dia.	Cap Type	Coupling Anchor Type	Mounting Screw No.	Finish Type
<b>WSO25-3/4 AL</b>	1" Dia. x 3/4" L	1/2" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-1 AL</b>	1" Dia. x 1" L	1/2" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-1-1/2 AL</b>	1" Dia. x 1-1/2" L	1/2" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-2 AL</b>	1" Dia. x 2" L	1/2" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-3 AL</b>	1" Dia. x 3" L	1/2" max	5/16"	Flat Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-3/4 AL/R</b>	1" Dia. x 3/4" L	1/2" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-1 AL/R</b>	1" Dia. x 1" L	1/2" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-1-1/2 AL/R</b>	1" Dia. x 1-1/2" L	1/2" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-2 AL/R</b>	1" Dia. x 2" L	1/2" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-3 AL/R</b>	1" Dia. x 3" L	1/2" max	5/16"	Round Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-3/4 AL/L</b>	1" Dia. x 3/4" L	1/2" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-1 AL/L</b>	1" Dia. x 1" L	1/2" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-1-1/2 AL/L</b>	1" Dia. x 1-1/2" L	1/2" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-2 AL/L</b>	1" Dia. x 2" L	1/2" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-3 AL/L</b>	1" Dia. x 3" L	1/2" max	5/16"	Low Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-3/4 AL/H</b>	1" Dia. x 3/4" L	1/2" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-1 AL/H</b>	1" Dia. x 1" L	1/2" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-1-1/2 AL/H</b>	1" Dia. x 1-1/2" L	1/2" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-2 AL/H</b>	1" Dia. x 2" L	1/2" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSO25-3 AL/H</b>	1" Dia. x 3" L	1/2" max	5/16"	High Profile Cap	M12 Threaded / Inside Fit	Require no. 8 screw	Clear Anodized
<b>WSB-1520 AL</b>	5/8" Dia. x 3/4" L	1/4" max	1/4"	15mm Dia.	Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-1525 AL</b>	5/8" Dia. x 1" L	1/4" max	1/4"	15mm Dia.	Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-1532 AL</b>	5/8" Dia. x 1-1/4" L	1/4" max	1/4"	15mm Dia.	Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-1538 AL</b>	5/8" Dia. x 1-1/2" L	1/4" max	1/4"	15mm Dia.	Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-2020 AL</b>	3/4" Dia. x 3/4" L	5/16" max	5/16"	20mm Dia.	*Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-2025 AL</b>	3/4" Dia. x 1" L	5/16" max	5/16"	20mm Dia.	*Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-2032 AL</b>	3/4" Dia. x 1-1/4" L	5/16" max	5/16"	20mm Dia.	*Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-2038 AL</b>	3/4" Dia. x 1-1/2" L	5/16" max	5/16"	20mm Dia.	*Require WB-TR	Require no. 8 screw	Clear Anodized

## Aluminum Standoff Supports - Specifications

Item Code No.	Item Dimensions	Panel Thickness	Panel Hole Dia.	Cap Type	Coupling Anchor Type	Mounting Screw No.	Finish Type
<b>WSB-2520 AL</b>	1" Dia. x 3/4" L	1/2" max	5/16"	25mm Dia.	**Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-2525 AL</b>	1" Dia. x 1" L	1/2" max	5/16"	25mm Dia.	**Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-2538 AL</b>	1" Dia. x 1-1/2" L	1/2" max	5/16"	25mm Dia.	**Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-2551 AL</b>	1" Dia. x 2" L	1/2" max	5/16"	25mm Dia.	**Require WB-TR	Require no. 8 screw	Clear Anodized
<b>WSB-2576 AL</b>	1" Dia. x 3" L	1/2" max	5/16"	25mm Dia.	**Require WB-TR	Require no. 8 screw	Clear Anodized
<b>SC-15 AL</b>	5/8" Dia.	1/4" max	1/4"	Flat Cap			Clear Anodized
<b>SC-20 AL</b>	3/4" Dia.	5/16" max	5/16"	Flat Cap			Clear Anodized
<b>SC-25 AL</b>	1" Dia.	1/2" max	5/16"	Flat Cap			Clear Anodized
<b>SC-15 AL/R</b>	5/8" Dia.	1/4" max	1/4"	Round Cap			Clear Anodized
<b>SC-20 AL/R</b>	3/4" Dia.	5/16" max	5/16"	Round Cap			Clear Anodized
<b>SC-25 AL/R</b>	1" Dia.	1/2" max	5/16"	Round Cap			Clear Anodized
<b>SC-15 AL/L</b>	5/8" Dia.	1/4" max	1/4"	Low Profile Cap			Clear Anodized
<b>SC-20 AL/L</b>	3/4" Dia.	5/16" max	5/16"	Low Profile Cap			Clear Anodized
<b>SC-25 AL/L</b>	1" Dia.	1/2" max	5/16"	Low Profile Cap			Clear Anodized
<b>SC-15 AL/H</b>	5/8" Dia.	1/4" max	1/4"	High Profile Cap			Clear Anodized
<b>SC-20 AL/H</b>	3/4" Dia.	5/16" max	5/16"	High Profile Cap			Clear Anodized
<b>SC-25 AL/H</b>	1" Dia.	1/2" max	5/16"	High Profile Cap			Clear Anodized
<b>WB-TR</b>	M12 Threaded Coupling				Use with any Standoff Barrel above	Require no. 8 screw	Solid Brass
<b>WB20-TR AL</b>	3/4" Dia. Base x 5/64" Depth				For mounting heavier applications	Require no. 8 screw	Clear Anodized
<b>WB25-TR AL</b>	1" Dia. Base x 5/64" Depth				For mounting heavier applications	Require no. 8 screw	Clear Anodized
<b>WB30-TR AL</b>	1-3/16" Dia. Base x 5/64" Depth				For mounting heavier applications	Require no. 8 screw	Clear Anodized
<b>WB30-TR AL/C</b>	1-3/16" Dia. Conical Base x 3/16" Depth				For mounting heavier applications	Require no. 8 screw	Clear Anodized
<b>WB35-TR AL/C</b>	1-3/8" Dia. Conical Base x 3/16" Depth				For mounting heavier applications	Require no. 8 screw	Clear Anodized
<b>PCW-AL</b>	M12 / M6 Threads						Nickel Plated

Material: Aluminum

Material Plating: Aluminum Anodized

\* For heavier applications use WB20-TR AL, or WB30-TR AL/C Wall Anchors

\*\* For heavier applications use WB25-TR AL, or WB35-TR AL/C Wall Anchors

Custom sizes or finishes are also available

1000 pieces minimum. Call for pricing and lead time.